

COSMO1000

1000FT LONG RANGE
WIRELESS HDMI/SDI
TRANSMISSION SYSTEM



1080P 60Hz
4:2:2



AES-128 ENCRYPTED
TRANSMISSION



SDI&HDMI
INPUT /OUTPUT



POINT TO POINT



NO COMPRESSION
NO DELAY

APPLICATION & FEATURES



- GUARANTEED DISTANCE:400FT, UP TO 700FT
- SDI&HDMI INPUT/OUTPUT
- NO COMPRESSION, NO DELAY
- TRUE FULL HD 1080P60; 4:2:2
- POINT TO POINT &MULTIPOINT
- 5GHZ FREQUENCY BAND
- WORKING VOLTAGE: 7-36VDC
- AES-128 ENCRYPTED TRANSMISSION
- WIDE RANGE POWER VOLTAGE 7-36V DC INPUT, ADAPT TO MOST KINDS OF CAMERA BATTERIES
- OPTIONAL SONY F970 BATTERY BUCKLE, CONVENIENT FOR FIELD BATTERY INSTALL AND REPLACEMENT

INTERFACE INTRODUCTION

RECEIVER:

- 1 RSSI(WIRELESS RECEIVED SIGNAL STRENGTH INDICATOR),5 GREEN LEDS
- 2 VIDEO INPUT INDICATOR,1 YELLOW LED
- 3 POWER ON INDICATOR,1 GREEN LED
- 4 FREQUENCY SELECTION KNOB,0-9
- 5 SDI OUTPUT
- 6 HDMI OUTPUT
- 7 DC POWER SWITCH
- 8 DC INPUT,LEMO 4-PIN B SERIES CONNECTOR



TRANSMITTER:

- 1 VIDEO INPUT INDICATOR,1 YELLOW LED
- 2 POWER ON INDICATOR,1 GREEN LED
- 3 FREQUENCY SELECTION KNOB,0-9
- 4 SDI INPUT
- 5 HDMI INPUT
- 6 DC POWER SWITCH
- 7 DC INPUT,LEMO 4-PIN B SERIES CONNECTOR

SIZE OF PRODUCT



PACKING LIST



PACKING CASE



SIZE:455*380*335MM
WEIGHT:0.8KG

A. EXTRA COSMO SET



► Cosmo Plate
Cosmo1000X
Wireless Video Transmission System

Enlarge distance from 1000ft,
Up to 2000ft to 3300ft
Just By Cosmo1000X Panel Antenna

B. APPLICATION



Cosmo1000X Panel Antenna, More info

<http://www.hollyland-tech.com/wireless.php?id=6>